



THERMOMAX

DF100

Direct Flow Vacuum Tube Solar Collector

The versatile solar water heating solution

The flexible installation options of DF100 collectors provide the perfect solution when the ideal position on the building is not available.

After over 25 years of manufacturing and development, Thermomax evacuated tube collectors are firmly established as a world leader in solar thermal products.

Easy Installation

The unique 'plug and play' design of Thermomax solar collectors makes installation quick and easy. There is no need for heavy lifting equipment as tubes can be carried onto the roof individually. The collector is fixed to the roof by easy-fit brackets, which are simply fixed to the rafter.

Performance and Savings

Designed specifically for Northern European climates, Thermomax products provide heat even in cold, windy or humid conditions

A superior vacuum in the tube, over a longer period of time

Supplies up to 70% of your annual hot water needs – reducing dependence on increasingly expensive fossil fuels

5 year standard warranty. 20 year warranty with a Kingspan Solar Accredited Installer

Works from dawn until dusk and throughout the year

30% more effective than flat plate collectors

Average 25-year lifespan

DF100 is a direct flow solar collector, which consists of a row of solar tubes and a highly insulated manifold. The heat medium to be heated is passed down through the collector tube within a coaxial heat exchanger.

The vacuum inside each tube provides perfect insulation and therefore protects the system from outside influences such as cold and windy weather or high humidity. This vacuum insulation also ensures that the energy collected from the sun is very efficiently and effectively transferred into usable heat



Chose DF100 for versatility

DF100 can be installed on a pitched or horizontal surface, and the tube can be rotated 25° to compensate for installations that deviate from south. As the collector is a fully pumped unit, there is no minimum angle for the collector.

Installation Options



Collector Positions

- 1 Ideal slope 40°
- 2 Roof kit angled 40°
- 3 Elevated 20°
- 4 Horizontal ideal slope
- 5 Horizontal façade
- 6 Flat
- 7 Vertical façade

DF100 collectors are available in 3 different sizes

	DF100		
	1m ²	2m ²	3m ²
Number of Tubes	10	20	30
Dimensions			
Absorber Area (m ²)	1.002	2.004	3.020
Overall Dimensions (mm)	1996 x 709 x 97	1996 x 1418 x 97	1996 x 2127 x 97
Width of Manifold (mm)	709	1418	2127
Length (tube and manifold) (mm)	1996	1996	1996
Depth (mm)	97	97	97
Aperture Area (m ²)	1.07	2.15	3.23
Fluid Volume (ltr)	1.8	3.6	5.6
Inlet and Outlet Dimensions (mm)	22	22	22
Weight (empty) (kg)	25	54.8	81.4
Mounting			
Recommended Inclination (°)	0-90	0-90	0-90
Performance Data			
Efficiency	Based on Aperture	Based on Aperture	Based on Aperture
Eta 0	0.781	0.773	0.779
a1 (W/m ² K)	1.44	1.43	1.07
a2 (W/m ² K ²)	0.0062	0.0059	0.0135
Solar Keymark Licence Numbers	011-7S060R	011-7S060R	011-7S060R
Operating Data			
Flow Rate (ltr/h)			
Rated	80	160	240
Minimum	60	120	180
Maximum	150	300	480
Maximum Operating Pressure	8 Bar	8 Bar	8 Bar
Stagnation Temperature (°C)	286	286	286
Heat Transfer Fluid	Water / Glycol	Water / Glycol	Water / Glycol
Materials			
Absorber	Copper	Copper	Copper
Coating	Selective Coating	Selective Coating	Selective Coating
Absorbance (%)	95	95	95
Emissivity (ε)	5	5	5
Mounting Frame and Clips	Stainless Steel, Aluminium, EPDM	Stainless Steel, Aluminium, EPDM	Stainless Steel, Aluminium, EPDM
Glass	Low Iron - Transm. 0.92	Low Iron - Transm. 0.92	Low Iron - Transm. 0.92
Vacuum	<10 ⁻⁶ mbar	<10 ⁻⁶ mbar	<10 ⁻⁶ mbar
Quality Certification/ Solar Keymark	Yes	Yes	Yes



KM 559829 BS EN 12975 Thermal solar systems and components

Contact us now for further information

Tel. +44 (0) 28 417 53031 or email us at info@nutechrenewables.com

NuTech Renewables Ltd, Unit11 Warrenpoint Enterprise Centre, Warrenpoint, BT34 3LA www.Nutechrenewables.com